

(a) K115HGLF Slate Gray
(b) K115HGXF / (c) K115HGXC\* Slate Gray
(d) K115HWLF White

(e) K115HWXF / (f) K115HWXC\* White (g) K115HGLP Slate Gray

(h) K115HGXP Slate Gray (i) K115HWLP White

-6° to 15°

(j) K115HWXP White

Engine Type H.O. Inline 3-Cylinder E-TEC G2 D.I.

Bore x Stroke - in (mm) 3.85 x 3.25 (98 x 82.6)

 Displacement - cu in (L)
 114 (1.9)

 Gear Ratio
 2.08:1

Full Throttle RPM Range 5000-6000 RPM

**Engine Model** 

Trim Range

(a)(d) 422 (191) (b)(e) 433 (196)) (c)(f)(h)(j) 408 (185) (g)(i) 397 (180)

 Starting
 Electric

 Controls
 ICON II

 Fuel Induction
 E-TEC Direct Injection with stratified low RPM combustion mode

Alternator Output\*\* Net Amps 14 idle / 22 wot

Steering (a)(b)(d)(e) DPS Power Assist (c)(f) Tie Bar/Remote (g)(h)(i)(j) Remote

Trim Method Power Trim & Tilt

Tilt Range 81°
(a)(d)(g)(j) 20 (508)

 Shaft Length - in (mm)
 (a)(d)(g)(1) 20 (308) (b)(c)(e)(f)(h)(j) 25 (635)

 Lubrication
 Multi-Point Targeted Oiling

Oil Tank Capacity - gal (L) 1.9 (7.2)

Recommended Oil XPS Marine XD100

Emissions Compliant

Mounting Centers - in (mm)

EPA 2013 / CARB 3 STAR / European Union

Minimum 26 (660)

 
 Color
 Over 400 Color Panel Options

 Steering Angle
 (a)(b)(d)(e) +/- 38° (c)(f)(g)(h)(i)(j) +/- 40°

Integrated Features Dual Axis Rigging / iTrim

- \* Corresponding Counter Rotation Model
- \*\* Current amp calculated at 13.5 V.
- † 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.

