

EVINRUDE® E-TEC® G2® 150 HP



7 panel colors and 14 accent stripe colors are available.
Slate Gray model shown with Orbital Blue panels and Swift Silver/Steel Gray accent stripes.
White model shown with Johnson White panels and Sea Foam/Swift Silver accent stripes.

Engine Model	(a) K150GLF Slate Gray (b) K150GXF / (c) K150GXC* Slate Gray (d) K150WLF White (e) K150WXF White / (f) K150WXC* White (g) K150GLP Slate Gray (h) K150GXP Slate Gray (i) K150WLP White (j) K150WXP White (k) K150GXT Slate Gray
Engine Type	Inline 3-Cylinder E-TEC G2 D.I.
Bore x Stroke - in (mm)	3.85 x 3.25 (98 x 82.6)
Displacement - cu in (L)	114 (1.9)
Gear Ratio	2.17:1
Full Throttle RPM Range	5000-6000 RPM
Weight - lbs (kg)	(a)(d) 422 (191) (b)(e)(k) 433 (196) (c)(f)(h)(j) 408 (185) (g)(i) 397 (180)
Starting	Electric
Controls	(a)(b)(c)(d)(e)(f)(g)(h)(i)(j) ICON II (k) Digital Tiller
Fuel Induction	E-TEC Direct Injection with stratified low RPM combustion mode
Alternator Output**	Net Amps 14 idle / 22 wot
Steering	(a)(b)(d)(e) DPS Power Assist (c)(f) Tie Bar/Remote (g)(h)(i)(j) Remote (k) Power Tiller
Trim Method	Power Trim & Tilt
Trim Range	-6° to 15°
Tilt Range	81°
Shaft Length - in (mm)	(a)(d)(g)(i) 20 (508) (b)(c)(e)(f)(h)(j)(k) 25 (635)
Lubrication	Multi-Point Targeted Oiling
Oil Tank Capacity - gal (L)	1.9 (7.2)
Recommended Oil	XPS Marine XD100
Recommended Fuel	87 Octane
Warranty	5-Year Engine† / 5-Year Corrosion
100% Global Emissions Compliant	EPA 2013 / CARB 3 STAR / European Union
Mounting Centers - in (mm)	Minimum 26 (660)
Color	Over 400 Color Panel Options
Steering Angle	(a)(b)(d)(e)(k) +/- 38° (c)(f)(g)(h)(i)(j) +/- 40°
Integrated Features	Dual Axis Rigging / iTrim

* Corresponding Counter Rotation Model

** Current amp calculated at 13.5 V.

† 3 years of BRP Limited Warranty and 2 years of BRP Extended Service Terms B.E.S.T.

©2019 Bombardier Recreational Products Inc. (BRP).
All rights reserved. ®, TM and the BRP logo are trademarks of BRP or its affiliates.

EVINRUDE®